

# graboSport SUPREME

Property

Standard

Unit

Result

## DESCRIPTION

Surface	-	-	TECH Surface
Backing	-	-	Closed cell double foam
Thickness	EN 428	mm	6,7
Weight	EN 430	kg/m <sup>2</sup>	3,8
Width	EN 426	m	2
Standard roll length	EN 426	m	15 ± 10%
Maximal roll length	EN 426	m	23

## CLASSIFICATION

Product specification	Vinyl indoor sport floor	EN 14904 (category P1)	
Impact sound insulation	EN ISO717-2	dB	22
Thermal resistance	-	m <sup>2</sup> K/W	0,07
Reaction to fire	EN 13501	-	C <sub>fi</sub> -s1
Formaldehyde emission	-	-	No formaldehyde
Pentachlorophenol	-	-	No pentachlorophenol

## SPORT PROPERTIES

Friction	EN 13036-4	-	80-110
Shock absorption	EN 14808	%	28
Vertical deformation	EN 14809	mm	1,08
Ball rebound	EN 12235	%	98
Specular gloss	EN 2813	%	< 30

## TECHNICAL CHARACTERISTICS

Dimensional stability	EN 434	%	± 0,2
Indentation resistance	EN 1516	mm	
Resistance to rolling load	EN 1569	N	1500
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN 423	-	no change
Abrasion resistance	EN ISO 5470-1	mg/1000cycles	< 250

## OTHERS

Limited warranty



15 years

Cleanability



TECH Surface - Easy to clean

Antimicrobial treatment



graboSAN

Environmental attributes



FloorScore certified:  
SCS-EC10.2-2007



No periodic renewal needed;  
Solvent and heavy metal free